

FLEXLED ROLL

24V, 5W, 3000K, 1 m, 60 LED/m

Flexible 24V DC LED strip for outdoor usage. For simplified mounting the backside is covered with adhesive tape. The power input is given by a 24V direct current power supply unit. We further offer accessory like feed cables, direct connectors and 90° soldering edges.

TECHNICAL DATA

Item no.:	552102
Nominal voltage	24V DC V
Length	100.0 cm
Width	1.0 cm
Height	0.3 cm
Net weight	0.015 kg
Gross weight	0.124 kg
IP Code	IP 20
Safety class	III
Wattage	5.0 W
Lumen	370 lm
Colour temperature	3000 Kelvin
Beam angle	120 °
CRI	>80
Binning	6
LED distance	1,7 cm
Service life	20000 h
Switching cycles	10000
<u> </u>	

							4				4			4		4		4	ч	4	4	ч	4	4	4	ч	4									
	a,	- 4		а	J	J	J.	J,	J	J.	J	J	J	J	J	a,	ä	J.	J.																	
ı J	J	ר ר	ı	J	J	J	J	J.	J	1	J	J.	J	J	J	J	J		ä			J		J.		1	J.	ı	J.	J	J.	ı	ı	L	١,	١,
					ы					а		а	a.	а	a.	а	а	л	J.	a.	1	J.	J.	ı	1		а	ы								



Accessories

470502	LED POWER SUPPLY , 12W, 24V
470502	LED POWER SUPPLY , 12W, 24V

Notes		