



FLEXLED ROLL

24V, 20W, 5700K, 5m, 60 LED/m

Flexible 24V DC LED strip for outdoor usage. For simplified mounting the backside is covered with adhesive tape. The power input is given by a 24V direct current power supply unit. We further offer accessory like feed cables, direct connectors and 90° soldering edges.

TECHNICAL DATA

Item no.:	552121
Nominal voltage	24V DC V
Length	500.0 cm
Width	1.0 cm
Height	0.2 cm
Net weight	0.044 kg
Gross weight	0.167 kg
IP Code	IP 20
Safety class	III
Wattage	20.0 W
Lumen	1850 lm
Colour temperature	5000 Kelvin
Beam angle	120 °
Color	copper
CRI	>80
Binning	6
LED distance	1,7 cm
Service life	20000 h
Switching cycles	10000
BIG WHITE Page	799

							4				4			4		-		4	4	4	4	ч	4	4	4	4	4									
	J,	_1		4	4	J	4	4	4	4	4	ı	ı	J	4	4	4	4	4																	
u	J	7 7	1	1	J	J	1	4	J	4	4	J	J	4	4	J	J		4			4		4		4	J.	J	J.	ı	a,	ı	ı	ı	ı	1
					ā			а		а		a.	a.	а	а	a.	a.	J.	J.	a.	a.	a.	J.	ı	ı	a.	а	а								



Accessories

470542	LED POWER SUPPLY , 20W, 24V
--------	-----------------------------

Notes			