



FLEXLED ROLL PRO

24V, 40W, 5000K, 3 m, 60 LED/m

High-performance flexible 24V DC LED strip of the PRO series . For simplified mounting the backside is covered with adhesive tape. The power input is given by a 24V PSU. This strip is available in several lengths and colours. Further available are connection leads, direct connectors and 90° soldering edges.

TECHNICAL DATA

Item no.:	552141
Nominal voltage	24V DC V
Length	300.0 cm
Width	1.0 cm
Height	0.2 cm
Net weight	0.055 kg
Gross weight	0.106 kg
IP Code	IP 20
Safety class	III
Wattage	36.0 W
Lumen	3060 lm
Colour temperature	5000 Kelvin
Beam angle	120 °
Color	white
CRI	>80
Binning	6
LED distance	1,7 cm
Service life	20000 h
Switching cycles	10000

							4				4			4		4		4	ч	4	4	ч	4	4	4	ч	4									
	a,	- 4		а	J	J	J.	J,	J	J.	J	J	J	J	J	a,	ä	J.	J.																	
ı J	J	ר ר	ı	J	J	J	J	J	J	1	J	J.	J	J	J	J	J		ä			J		J.		1	J.	ı	J.	J	J.	ı	ı	L	١,	١,
					ы					а		а	a.	а	a.	а	а	л	J.	a.	1	J.	J.	ı	1		а	ы								



Accessories

470544	LED POWER SUPPLY , 36W, 24V
--------	-----------------------------

Notes		