



DELFC 1000 PRO

light bar, 24V, 60 LED, 3000K

A rigid 24V DC LED RGB profile made from anodized aluminium and plastic. We included a connection lead, a flexible connector and mounting clips. Through the built-in plug-contacts these profiles can be connected directly to each other. The power-input to these profiles, available in several lengths, is made via a separately available 24V direct current power supply. This luminaire contains built-in LED lamps.

TECHNICAL DATA

Item no.:	631462
Lamps included	0
Primary nominal voltage	24V mA/V
Nominal voltage	24V DC V
Length	100.4 cm
Width	2.0 cm
Height	1.5 cm
Net weight	0.205 kg
Gross weight	0.261 kg
IP Code	IP 20
Safety class	III
Safety class	III
Assembly	Surface
Assembly details	Ceiling,Ground,Wall
Wattage	12.0 W
Lumen	900 lm
Colour temperature	3000 Kelvin
Beam angle	120 °
Color	aluminium
CRI	>80
Binning	6
Binning	6

Accessories

470502	LED POWER SUPPLY , 12W, 24V
631470	FEED-IN CABLE , for DELF C PRO light bar single-colour, max. 50W, 1.5m
631471	FLEXIBLE CONNECTOR , for DELF C PRO light bar single-colour, max. 50W, 12cm
631472	MOUNTING CLIPS , for DELF C PRO light bar, 10 pieces
631475	MOUNTING CLIPS , for DELF C PRO light bar, 10 pieces, 45°

LXXBXX data	70/50
Service life	20000 h
Service life	20000 h
Ambient temperature	40 °C

Notes
