



## DELFC 1000 RGB PRO

light bar, 24V, 60 LED

A rigid 24V DC LED RGB profile made from anodized aluminium and plastic. We included a connection lead, a flexible connector and mounting clips. Through the build-in plug-contacts these profiles can be connected directly to each other. The power-input to these profiles, available in several lengths, is made via a separately available 24V direct current power supply. To control the RGB-effects, a controller is required and available as an accessory. This luminaire contains built-in LED lamps.

### TECHNICAL DATA

Item no.:	631463
Lamps included	0
Primary nominal voltage	24V mA/V
Nominal voltage	24V DC V
Length	100.0 cm
Width	2.0 cm
Height	1.5 cm
Net weight	0.207 kg
Gross weight	0.271 kg
IP Code	IP 20
Safety class	III
Safety class	III
Assembly	Surface
Assembly details	Ceiling,Ground,Wall
Wattage	15.0 W
Color	aluminium
CRI	>80
LXXBXX data	70/50
Service life	20000 h
Service life	20000 h

## Accessories

470520	REMOTE CONTROL , for POWER LIM@ 2 master controller, incl. IR receiver
470581	POWER LIM 2 RGB MASTER CONTROLLER , 24V, incl. power supply 60W
470582	POWER LIM 2 RGB SLAVE CONTROLLER , 24V incl. power supply 60W
631472	MOUNTING CLIPS , for DELF C PRO light bar, 10 pieces
631473	FEED-IN CABLE , for DELF C PRO light bar RGB, max. 50W, 1.5m
631474	FLEXIBLE CONNECTOR , for DELF C PRO light bar RGB, max. 50W, 12cm
631475	MOUNTING CLIPS , for DELF C PRO light bar, 10 pieces, 45°

## Notes

---

---

---

---

---