



DELF D

light bar, 6 LED, 3000K, L/W 10.5/1.5 cm, 24V

SLV DELF D filigree, modular plug & play light bar system made of anodised aluminium and plastic. Feed-in cables, flexible connectors and mounting clips are available as accessories. Thanks to the built-in plug contacts, the profiles can be connected directly to each other. The electrical connection of the profiles, which come in several lengths, is done to a separately available 24V DC power supply. This luminaire includes built-in LED lamps.

TECHNICAL DATA

Item no.:	631501
Lamps included	0
Primary nominal voltage	24V mA/V
Length	10.5 cm
Width	1.5 cm
Height	1.4 cm
Net weight	0.028 kg
Gross weight	0.035 kg
IP Code	IP 20
Safety class	III
Assembly	Surface
Assembly details	Ceiling, Ground, Wall
Wattage	1.5 W
Lumen	105 lm
Colour temperature	3000 Kelvin
Beam angle	110 °
Color	aluminium
CRI	>80
Binning	3
LXXBXX data	70/50
Service life	30000 h
Minimum ambient temperature	-20 °C

Maximum ambient temperature	40 °C
BIG WHITE Page	813

Accessories

470502	LED POWER SUPPLY , 12W, 24V
470547	TCI LED POWER SUPPLY , 20W, 24V, incl. strain relief

Notes
